



(763) **502-0000** WWW.STREAMFEEDER.COM INFO@STREAMFEEDER.COM

C F

Specialty Packaging Series Streamfeeder ST-1450 High-Speed Collator Feeder

Overview

The ST-1450 was designed for inline applications where machine footprint is limited. It's compact footprint requires less than 16" of mounting area end to end. The feature-rich iQuipped Intelligent System Controller provides high performance operation with user-friendly menus. The ST-1450 is ideal for use in many applications and easily integrates mechanically and electrically for increased system efficiency.

Feed a wide variety of flat and multi-thickness products into shrink wrappers, poly baggers, banders, collators, case packers, boxes, and more. Operates on-demand one at a time or in batch sets up to 9999 pieces.

Standard Features

Vacuum fluorescent display with easy to use menus . Long-lasting natural rubber feed belts with vacuum assist • One-knob side guide positioning • Patented advancing O-ring separator for product separation • Tool-less discharge angle adjustment • Self-adjusting discharge hold down • Variable speed control • Batch counting capabilities • Miss-detect • Timeout stop • Photo-sensor trigger input • Double-sheet detection • Isolated inputs / outputs for system integration • Trigger delay • Self- triggering feature for stand-alone operation • Stainless steel construction

Applications (ask us about your application)

| Shrink Wrappers | Flow Wrappers | Inserter Open Track |
|-----------------|-------------------|---------------------|
| Poly-baggers | Cartoners | Collators |
| Case Packers | Order Fulfillment | |

| Products (ask us about your products) | | |
|---------------------------------------|-----------------|-------------------|
| Sheet Paper | Backer Board | Folded Documents |
| Manuals | Literature Kits | Folders |
| Cardstock | Envelopes | Booklets |
| Retail Signage | Brochures | Collapsed Cartons |
| and more | | |



| Specifications | |
|------------------------------|--|
| Maximum Product Size | 14 W x 9 L in (356 x 229 mm) Optional: 14 W x 14 L in (356 x 356 mm) |
| Minimum Product Size | 3.75 W x 2.5 L in (95 x 64 mm) Optional: 2 W x 2.25 L in (51 x 57 mm) |
| Min/Max Product Thickness | .003 - 1.00 in (.076 - 25.4 mm) |
| Belt Speed | 5500 in/min (140 m/min) |
| Batch Size | 1-9999 |
| Utilities | 115/230vac, 50/60Hz, 3A |
| Weight | 84 lbs. (38 kg) including control panel |
| Warranty | One year limited |
| Other sizes and thickness of | capabilities available. Contact us for your application. |

FOOTPRINT DRAWING AVAILABLE AT: www.streamfeeder.com/footprints.html



or scan the QR Code



NIGRELLI HUDSON-SHARP



