

# The Domino DDC3

*The third generation digital laser coder that sets new levels of reliability and versatility, and offers an even wider range of capability.*




## A Reputation for Reliability

With a heritage of unmatched reliability, the DDC3 was developed to eliminate unplanned downtime. It incorporates Domino's exclusive sealed CO<sub>2</sub> laser tubes, designed and manufactured in-house and proven on the world's production lines. This air-cooled coding system operates without moving parts or consumables, ensuring virtually maintenance free coding. It features state-of-the-art power-supply technology for cooler operation and ultimate system reliability. While the IP56/NEMA4 control cabinet provides protection against the most extreme working environments, the remote laser head is shock resistant and features new self-aligning optics that eliminate time intensive adjustments.

## Extended Flexibility by Design

Domino's exclusive Rainbow™ laser tubes allow high quality coding on a wider range of substrates. Within each selectable range, laser power can be custom tuned, using the integrated control panel, to the precise level needed for your coding application. From the hardest industrial ceramics to the thinnest PET or thermoplastics, your products can be reliably and consistently coded without perforating the material. The digitally generated characters are permanent and completely indelible. The DDC3 is fully programmable, delivering higher efficiency at far lower, safer power levels. The small footprint of the control cabinet and the exclusive choices of two long, flexible umbilicals, 14 feet (4.3m) or 38 feet (11.5m), allow the slim print head to be fitted and positioned anywhere on the production line. Single head, or Domino's exclusive dual head models are capable of printing up to two lines per head without loss of coding speed, and can code without distortion onto curved surfaces like the neck of a bottle.




## Easy to Use

Designed with today's busy operator in mind, the colour VGA display and WYSIWYG software simplify operation. It is easy to set up or change codes using the full sized keyboard. Special "HOT" keys are also available for the most frequently used functions.

## Costs Less to Operate and Maintain

The sealed CO<sub>2</sub> laser tubes eliminate the need for consumables and water cooling systems and are designed for years of trouble free operation. Direct high efficiency optics enable superior coding at far lower power levels without the need for moving parts.



High speed coding



Ideal for labels and flexible packaging




## Technical Specifications:


<b>Laser type:</b>	Sealed CO <sub>2</sub> RF excited, gas consumption nil
<b>Data entry and display:</b>	Video user interface with integrated control panel and color VGA screen
<b>Lines of text:</b>	Up to two lines per head
<b>Character generation: (substrate dependent)</b>	Up to 2000/sec (single line) or 4000/sec (twin line); up to 3300/sec (single line) or 6600/sec (twin line) with LEEP laser tubes
<b>Line speed (substrate dependent):</b>	820ft/min (250m/min) 1310ft/min (400m/min) – LEEP lasers
<b>Print formats:</b>	5x5, 7x5, 7x9, PC font, Arabic font
<b>Character height range:</b>	0.04" up to 0.40" (1.0mm up to 10mm)
<b>Standard Software features:</b>	Sequential numbering, batch numbering, full clock options, password protection, user defined symbols, WYSIWYG message entry
<b>Message length:</b>	Up to 253 characters per message
<b>Inputs:</b>	Shaft encoder, product detector, external interlocks, fume extraction status monitoring, plus two userconfigurable inputs
<b>Interface:</b>	RS232 std., RS422 or RS485 optional
<b>Outputs:</b>	Three colour status beacon kit, 3 voltage free relays suitable for interface to line stop, Voltage free relays for controlling fume extraction and compressed air laserhead cooling, Two user-configurable outputs
<b>Flexible conduits:</b>	14" (4.3m) and 38" (11.5m)
<b>Power requirements:</b>	100-240 VAC, 6A, 50-60Hz (single head) 100-240 VAC, 12A, 50-60Hz (dual head)
<b>Air cooled laser head:</b>	Plant air required typically 3.5 SCFM (100 litre/min) at 10psi minimum (duty cycle and ambient temperature dependent)
<b>Control cabinet cooling:</b>	Ambient air-cooling with optional fan pack may be required for high duty cycle and high ambient temperature
<b>Environmental standard:</b>	IP56, NEMA 4
<b>Operating temperature:</b>	41-113°F (5-45°C)
<b>Humidity:</b>	10-100% non-condensing (operating)
<b>Cabinet:</b>	Stainless steel
<b>Dimensions:</b>	30.5" high X 17.1" wide X 18.6" deep (775mm high x 435mm wide x 472mm deep)
<b>Weight:</b>	Approx. 146lbs (66kg)
<b>Regulatory Standards:</b>	TÜV, CDRH, CE mark

## Dimensions:

Cabinet



Laser print head



**Australia**  
Domino (Australia) Pty. Ltd.  
Unit 12  
6 Gladstone Road  
Castle Hill  
Sydney  
NSW 2154  
Tel: + 61 2 9894 7833

**Canada**  
Domino Printing  
Solutions Inc.  
2751 Coventry Road  
Oakville  
Ontario  
L6H 5V9  
Tel: + 1 800 387 7972

**India**  
Domino Printech India  
Private Limited  
167, Udyog Vihar Phase I,  
H.S.I.D.C Gurgaon -  
122016 Haryana  
Tel: + 91 124 400 7406

**United Arab  
Emirates**  
Domino UK Ltd (Dubai)  
PO Box 16984  
Jebel Ali  
Dubai  
Tel: + 971 4 88 35003

**United Kingdom**  
Domino UK Ltd  
Bar Hill  
Cambridge  
CB23 8TU  
Tel: + 44 1954 782 551

**United States of America**  
Domino Amjet, Inc.  
1290 Lakeside Drive  
Gurnee  
Illinois 60031  
Tel: + 1 800 486 7414



[www.domino-printing.com](http://www.domino-printing.com)

UK: Cert. No. FM 13758  
BS EN ISO 9001

