

Hess Machine International
 PO Box 639, USA
Phone: 800.735.HESS or 717.733.0005
Fax: 717.733.2255
Email: ozone@hessmachine.com

Item # L-200-T-150, L-200 Ozone Generator with T-150 Injection Tank



L-200 Ozone Generator with T-150 Injection Tank

Gallons per Minute - 90/120*
 Gallons per Hour - 5400/7200*
 Click through to see full Flow Rates
 * - with T-300 Injection Tank

SPECIFICATIONS

Injection Tank Type	T-150
Ozone Yield	2 lbs./day
Ozone Yield	38 g/hour
Generator Width	30 inches
Generator Length	68 inches
Generator Height	48 inches
Generator Weight	365 lbs.
Shipping Width	40 inches
Shipping Length	72 inches
Shipping Height	54 inches
Shipping Weight	550 lbs.
Volts	110 V 220 V
Frequency	50 Hz 60 Hz
Current	20 A
Phase	1

Plug-in Electrical Cord	No
Electrical Fused Disconnect	Yes
High Current Breaker	20 A
High Voltage Transformer	2 KVA
Maximum Air Flow	2 SCFM
Maximum Air Flow	120 SCFH
Air Pressure Into Dryer	80 psi
Air Pressure Out of Dryer	13 psi
Power (Oil-Free Air Compressor)	1 HP
Voltage (Oil-Free Air Compressor)	110 V 220 V
Desiccant Cell Size	9 inches
Moisture Indicator	Yes
Required Flow (Cooling Water)	20 gph