

# SHIPMATE SKIN PACKAGER by Ampak

MODEL: SP1824 A or B



## FEATURES

### CONTROL PANEL

- PLC with Color HMI Controls
- Adjustable Pre-Heat, Heat And Cool Package Time Functions

### HEATING OVEN

- Stationary Oven With Safety Guard
- Patented Spirad Instant-On Heating Elements
- Adjustable Oven Height

### SEALING PLATFORM

- Variable Speed Turbine Vacuum System
- Pneumatic Film Frame Drive

### OTHER FEATURES

- Spindle Film Roll Holder
- One Year Warranty



## MODEL SPECS

<b>PLATEN SIZE</b>	18" W, 24" L (46 W, 61 L cm)
<b>PLATEN CLEARANCE</b>	Factory Adjustable 9"-20" (23-51 cm); Standard Setting 19" (48 cm)
<b>PLATEN HEIGHT</b>	40" (102 cm)
<b>FILM CAPACITY</b>	20" W, 9" OD, 3" ID (51 W, 23 OD, 7.5 ID cm)
<b>OVERALL DIMENSIONS</b>	39" L, 43" W, 60" H (99 L, 109 W, 152 H cm)
<b>POWER REQUIREMENTS</b>	208/220 Volt, 41/39 Amps, Single Phase (Three Phase Available)
<b>AIR REQUIREMENTS</b>	1 CFM @ 80 PSI
<b>VACUUM</b>	(A) Hivac Turbine 96 cfm, 6.5" Hg.; (B) Turbine plus 1/4 HP Pos. Disp. Pump, 21 Gal. Tank, 25" Hg.
<b>WEIGHT</b>	(A) 500 lbs. (190 kg); (B) 575 lbs. (227 kg)

## AVAILABLE OPTIONS

- Positive Displacement Vacuum System (SP1824B)
- Electro-Pulse Film Cutoff
- Energy Miser Film Temperature Sensing System
- Extended Cooling Cycle for Energy Miser Probe
- Transformer For 440-480 Volts
- 2 Foot Bolt On Infeed/Outfeed Table
- Special Size Frame Insert And Platen
- Automatic Blowoff System For Vacuum Forming - Positive Displacement System Only
- 6 Foot Infeed/Outfeed Freestanding Table
- Automatic Film Frame
- Automatic Platen Lift
- Automatic Infeed And Outfeed System
- Automatic Outfeed Electrical Interface
- Spare Parts Kit

Revised 2013

