

FORMOST FUJI

FUJI-FORMOST ALPHA WRAPPER

Quality is "First and Formost"



ALPHA WRAPPER

FUJI-FORMOST MODEL FW-3462
HORIZONTAL STRETCH SHRINK FILM
WRAPPER WITH SHRINK TUNNEL



SUPERIOR, LEAK-PROOF SEALS

SMALL SYSTEM FOOTPRINT

ACCURATE REGISTRATION CONTROL

FAST, EASY CLEANING

AUTO INDEXING BELT

PACKLESS OPERATION

INNOVATIVE STRETCH/SHRINK WRAPPER

The Fuji-Formost model FW-3462 Horizontal Stretch Shrink Film Wrapper is designed for use with the new generation of stretch/shrink films to provide fully sealed leak-proof packages for trayed products.

The trays are fed into the wrapper by an auto-indexing belt infeed. The machine pulls the film around the tray creating a center seal underneath the tray. Box motion end sealers are used for close, tight wrapping. Trimming of the center seal is also available. The package then travels through the shrink tunnel which pulls the film against the tray, creating a tight, neat, sealed package.

FORMOST FUJI CORPORATION

19211 144th Avenue NE • Woodinville, WA 98072

Phone: 425-483-9090 • Fax: 425-486-5656 • email: salesoffice@formostfuji.com

www.formostfuji.com

Package Advantages

Hygienic Pack Integrity

- Leak-proof seals
- Tamper evident packaging

High Consumer Appeal

- Package can be printed on all sides
- Neat, store wrapped appearance

Cost Effective

- Printability can eliminate sleeves and labels
- Can accommodate a variety of tray types and sizes



Specifications

| Machine Model | | FW-3462 | FW-3462W |
|-----------------|----------------|---------------------|------------------|
| Operating Speed | | 15-80 packs/min | 15-60 packs/min |
| Film | Width | 21 5/8" Max. | 27 1/2" Max. |
| | Length | 3 15/16" - 14 3/16" | 5 1/8" - 16 7/8" |
| Tray Dimensions | Width | 2 15/16" - 8 1/2" | 4 5/16" - 9 7/8" |
| | Height | 3/8" - 1 9/16" | 9/16" - 2 3/8" |
| | Product Height | 5 1/2" Max. | 3 3/8" Max. * |

* Based upon maximum tray width.

These specifications may vary according to special applications. Specifications are based upon the latest information available at the time of publication. Formost reserves the right to make changes in materials, equipment and specifications without prior notice.

FORMOST FUJI CORPORATION

19211 144th Avenue NE • Woodinville, WA 98072

Phone: 425-483-9090 • Fax: 425-486-5656 • email: salesoffice@formostfuji.com

www.formostfuji.com

Optional Features

- Gas Flushing
- Shrink Tunnel, Hot Air or Hot Air/Water Shrink Systems*
- Registration System for Printed Films
- Center Seal Trimming
- Air Curtain Dryer

* Shrink system required. System will be determined by product characteristics.

