



- HOPPER COVER WITH BULK BAG INTERFACE CHUTE
- INTERFACE CHUTE HAS DUST TIGHT SNAP ACTION DOOR FOR EASY ACCESS TO BULK BAG OUTLET SPOUT
- ACCESS PORT HAS SLOPED LOWER SILL TO ELIMINATE BUILD UP OF MATERIAL AT THE SNAP ACTION DOOR

-MODEL NUMBER: CVD-C30-X
-SERIAL NUMBER: 73102,

- TYPE "J" FLOOR HOPPER
- DESIGNED FOR POWDERY, SEMI-FREE FLOWING MATERIALS
- 5 CUBIC FOOT MEASURED CAPACITY
- MEASURES 30" SQUARE X 66-3/4" HIGH WHEN SUPPORTED BY ROTARY VALVE
- INCLUDES FLANGED OUTLET TO MATE WITH ROTARY VALVE
- INCLUDES GROUNDING LUG

Model #: HPJ2-C30-X

- PNEUMATIC CONVEYOR FLOW THROUGH PICK-UP ADAPTER
- DESIGNED TO ALLOW FOR EFFICIENT MATERIAL TRANSFER FROM A ROTARY VALVE INTO THE CONVEYING LINE
- MODIFIED FOR USE WITH A 22" ROTARY VALVE
- INCLUDES SUPPORT STAND TO SUPPORT 22" ROTARY VALVE AND HOPPER ASSEMBLY
- DESIGNED TO MATE WITH A 6" O.D. CONVEY LINE.

Model #: PAF2-C-X

- 15 INCH DIAMETER IRIS VALVE WITH POLY-NYLON DIAPHRAGM
- FULLY NOTCHED, CAST ALUMINUM BODY ALLOWS FOR INCREMENTAL VALVE POSITIONING
- MANUALLY OPENED AND CLOSED WITH HAND OPERATED WHEEL
- USED TO SAFELY OPEN BULK BAG AND CONTROL FLOW FROM BULK BAG OUTLET SPOUT

- Model #: IVM-15

- PNEUMATIC TURBINE VIBRATOR ASSEMBLY
- REQUIRES 60-80 PSI AIR SUPPLY

Model #: VBP-W

- 22" DROP THROUGH DESIGN ROTARY VALVE
- DESIGNED TO PROVIDE METERED FLOW OF MATERIAL TO DOWNSTREAM PROCESS EQUIPMENT UNDER AIRLOCK CONDITIONS
- 2 HP, 1725 RPM, 3 PHASE, 60 HZ, TEFC MOTOR WITH GEAR REDUCTION UNIT
- INCLUDES (8) VANE OPEN END ROTOR WITH BEVELED EDGES
- 15 PSIG MAXIMUM PRESSURE DIFFERENTIAL
- INCLUDES CHROME PLATING ON INTERNAL VALVE BODY AND END COVERS, AND ROTOR SHAFT

ROTARY VALVE SPEED: 10 RPM
MATERIAL THROUGHPUT: 6800 LBS/HR
Model #: RVD-C12T-X