

CSX Series

Fully Automatic Random Sidedrive

The BestPack™ CSX Series Fully Automatic Random Carton Sealer's advanced engineering provides the high speed output, and are built for rugged dependability. The CSX design uses three independent operating stations that include the Centering Station, Folding Station, and Sealing Station. For operational dependability and performance, maintenance free oil-less air cylinders are used. These features along with others in our CSX Series set BestPack apart from others in the marketplace. These sealers are designed to meet all your operator free random carton sealing applications.

All systems incorporate our exclusive 2" or 3" pop out pressure sensitive "High Speed" tape heads with patented tab adjustment. All BestPack units are available in our standard baked enamel finish or food grade 304 stainless steel for 21 CFR 110 compliance. Custom sizes available for your application.



Key Points of the Carton Sealer



Does Not Require Operator



Random Cartons



Top & Bottom Seal

Features

- Heavy Duty 3mm Welded Frame
- Omron PLC Logic
- Independent Random 3-stage Operation: Centering, Flap Folding, & Sealing
- Random Side Belt Drive with High Speed Motors
- Random Upper Side Compression Rollers
- Interlock Safety Gates
- Capable of Interchanging 2" or 3" BestPack High Speed Tape Heads
- Low Tape/No Tape on Carton/No Cut Sensors & Alarm with Warning Light
- SMC Maintenance Free, Oil-less Air Cylinders with Air Cushion
- Electrical Panel and Air Adjustments are Left Justified (Unless otherwise ordered)

- Tape Roll Lengths: 1,000 yd. & 1,500 yd.
- UL Approved Electrical Parts
- Heavy Duty Casters
- Operation Manual with Tools

Options

- Food Grade 304 Stainless Steel
- Retractable Top or Bottom Tape Heads
- Touch Screen Human Interface
- User Specified PLC Brand
- Exit Conveyor

Extra Accessories to Improve Efficiency



Spare Parts Kit May Vary

Spare Parts Kit



Exit Conveyor w/ Stopper



Spare Tape Head



Carton Sealing Tape

- Food Grade 304 Stainless Steel

Machine & Carton Specifications

110 Volts 60 Hz

Power Requirements

Up to 12 Cartons/min.

Speed

100 PSI

12+ SCFM
Air Requirements

1,320 lbs

Shipping Weight

Model	Machine Dimensions Length x Width x Height	Carton Range* Length (min. - max.) x Width (min. - max.) x Height (min. - max.)	Conveyor Height Adjustment Height (min. - max.)	Cartons per min.	Shipping Weight (lbs.)
CSX22-2H 2" Tape Head	(95.8") x (40.0") x (90.5")	(9.0" - 25.0") x (6.3" - 20.5") x (5.5" - 22.0")	Determined at the time of order	Up to 12	1320
CSX22-3H 3" Tape Head	(95.8") x (40.0") x (90.5")	(9.0" - 25.0") x (6.3" - 20.5") x (5.5" - 22.0")	Determined at the time of order	Up to 12	1320

Information subject to change without notice.

*Outside Dimensions Only