

> CONVERTIBLE STOCK

- > Corrugated board 0,75 - 9 mm (1/32" – 3/8")
- > Solid board (depending on quality), from 0.75 mm (1/32")

> SIZES

- > Sheet size, max. 1600 x 1100 mm (63" x 43 1/4")
- > Sheet size, min. 600 x 520 mm (24" x 20 1/2")
- > Sheet size, min. for SPO 160-A Power Register 700 x 520 mm (27 9/16" x 20 1/2")

> DIECUTTING

- > Cutting size, max. 1600 x 1075 mm (63" x 42 5/16")
- > Height of cutting rules 23,8 / 28,57 mm (.937" / 1 1/8")
- > Adjustable gripper margin 15 + 3 / - 6 mm (5/8" +1/8" / - 1/4")
- > Cutting force, max. (400 t) 4 MN
- > Batch height at delivery, max. 250 mm (10")
- > Production speed for SPO 160-A 6'750 SPH
- > Production speed for SPO 160-A Power Register 6'500 SPH



> OVERALL DIMENSIONS

> Length	9,2 m	(30 ³ / ₁₆ "
> Width SPO platen (with platform)	7,1 m	(23 ⁵ / ₁₆ "
> Height	3,0 m	(9 ⁷ / ₈ "

> WEIGHT

> Weight	32 t	(33.1 US tons)
----------	------	----------------