

LANTECH SW1000

**INTERMITTENT MOTION, BELTED INFEED
SIDE-SEAL SHRINK WRAPPER**

**DESIGNED TO MAKE SET-UP
AND OPERATION AS SIMPLE
AS POSSIBLE TO INCREASE
PRODUCTIVITY**

LANTECH ROTARY SIDE-SEAL

- Separate cut and seal process eliminates film build-up. No cleaning required.
- Handles infinite product lengths.
- Positive cut and seal process is ideal for polyolefin, PVC and LDPE films.
- Handles wide temperature and speed ranges.
- One-step temperature set-up. No pressure, dwell, angle adjustments needed.



SW-1000



SURE-TRAC FILM DELIVERY SYSTEM

- On-the-fly film adjustments reduces downtime.
- Sure-Trac electronic film drive eliminates film breaks and allows narrow trim to reduce film waste.
- Easy film roll placement and threading.

CREATE YOUR OWN SYSTEM

Configure and price a stretch wrapper at www.codepack.cl

ST-900



Lantech.com

Lantech SW1000 *Specifications*




FIT TO APPLICATION

- Right-to left flow (standard).
- Adjustable inverting head.
- Random product lengths.
- Vertical product detection.
- Wide variety of standard infeeds; flight bar, flight lug, belt.
- Perfect match with ST-Series "soft convection" Shrink Tunnels.

OPERATOR - FRIENDLY

- Programmable Logic Controller.
- Color touch-screen control panel with password protection.
- Store and recall set-up parameters.

Standard operating height range 32"-38"



SW-1000 Shrink Wrapper shown with Lantech ST-700 Shrink Tunnel.

SW1000 - SPECIFICATIONS

PRODUCTION SPEED- FEET/MINUTE	up to 90	PNEUMATIC REQUIREMENTS	5-8 CFM @ 85 PSI
- PACKAGES/MINUTE	up to 40	COLOR TOUCH SCREEN HMI	Top level access to primary machine functions, changeable without stopping machine Password Protection (3 levels) Easily store and recall up to 16 basic recipes Diagnostic and maintenance features
MACHINE TYPE	Intermittent motion	MULTIPLE OPERATING MODES SELECTABLE THROUGH HMI	Intermittent or Continuous infeed Multipack or single package mode tall package 0-90 fpm Horizontal/Vertical photo-eye
INFEED CONVEYOR	15" W BELT	WEIGHT (approx. machine/shipping)	1600 / 2200 lbs.
PRODUCT SIZES (L X W X H) MIN	3" x 1" x 1/8"	OPTIONS	Casters, Pre-spacing conveyor, Horizontal photo-eye, Print Registration, Exit transition rollers, Film support inverter rods, Film Centerfolder, Adjustable infeed guide
(L X W X H) MAX*	Infinite X 15" X 8"	SERVICE/SUPPORT	24 hours - 7 days/week
	* NOTE: Maximum dimensions May not run simultaneously.	WARRANTY	1 Year
CROSS SEAL TYPE	Hot knife	(except consumable wear items)	
CROSS SEAL WIDTH	18"		
FILM WIDTH (CENTERFOLDED)	6" to 24"		
FILM TYPES	Most Commercial grade Polyolefin, PVC, LDPE. Some films may require change parts.		
TRIM WINDER	Mechanical with Electronic Tension control		
ADJUSTABLE FILM INVERTING HEAD	STD		
CONTROLS	PLC/Touchscreen		
ELECTRICAL REQUIREMENTS	230 V, 1 phase, 15 Amp		

Also available: SW-2000 Continuous Motion Belted Infeed and SW-3000 Continuous Motion Flighted Infeed Wrappers