




CCW-RV-214W-1S-30-SS-PST1

Dedicated range of automated, high speed, accurate weighing solutions specifically designed for handling **PASTA**.

The RV series from Ishida represents the latest state of the art multihead weighing performance for speed, accuracy and reliability and comes with the industry's leading high performance specification as standard.

This multihead weigher range is designed specifically for weighing dry, free flowing short cut pasta at lower and medium target weights but at high speeds. This has been developed based on an unrivalled global installed base within this sector.

The Ishida pasta weighers have been thoroughly tested to ensure Ishida customers receive the best in class solution for this challenging application.



Specifications	CCW-RV-214W-1S-30-SS-PST1	
Weighing Capacity/Range (per head)	500g	1000g
Maximum Volume for Weighing (per dump)	4.5 litres	
Weighing Speed (variable dependent on specific product and target weight)	100 WPM	
Minimum Graduation	0.1g	0.2g
Touch Screen 3D Graphical Display (RCU)	12.1" Colour LCD display including printer (as standard)	
Weigh Cell	Ishida double-beam loadcell	
Vibration control on DFT and RFTs	Pulse width modulation (precise and programmable vibration frequency control - independent from input frequency)	
Number of Presets	200	
Materials	Hex and plain 304 stainless steel contact parts to control and encourage flow of product	
Machine Weight	Approx. 550kg	
Options	This pasta weigher model is a fixed high specification solution dedicated to the specific industry requirements (see specific model details)	
IP test rating of structure	IP54 (see specific cleaning instructions in operators manual)	
Power consumption	0.5kW	
Standard compliance	Ce/UL/FDA/USDA/RoHS	

Design and specifications are subject to change without notice (please confirm dimensions at point of order).











CCW-RV-214W-1S-30-SS-PST1



RV PASTA 1

Features and benefits



Part of a dedicated range of automated, high speed, accurate weighing solutions specifically designed for handling pasta using Ishida's unrivalled industry experience.

No other multihead weigher supplier can match the experience and global installed base of Ishida and it is this expertise and sector-specific knowledge that has gone into the pasta solution.

The pasta solution is based on the highest performance RV series multihead weigher platform – this has then been configured for optimum performance for this sector.

Detailed analysis of historic installations, combined with Ishida's expert team of design and application specialists has resulted in the creation of this range of high performance sector solutions.

RV high performance features

- Capable of using all 14 heads in a single combination calculation = 16383 combinations (for maximum efficiency and minimum product giveaway per cycle)
- Simultaneous triple combination calculation (delivering up to 100% efficiency)
- 5 stage digital filter (rapid stable calculations)
- Pulse width modulation on individual radial feeders (precise programmable vibration control to achieve harmonic frequency per radial feeder - independent of input frequency for unrivalled productspecific in-feed control)
- Average weight control software internal calculation resolution to 0.01g (minimise giveaway every cycle)
- Anti-floor vibration with 4 load cells (remove back ground vibration noise from load cell calculation for maximum weighing accuracy and avoiding product giveaway or missed cycles)

- 12.1" remote control unit (RCU) (large clear screen for rapid programmable control)
- RCU cover as standard (reduce risk of screen damage for long life)
- 200 different product pre-sets (flexible and ensures rapid product changeovers)
- 3D screen display with immediate screen refresh rates (clear intuitive data display to assist operator to continuously monitor and adjust machine performance)
- Ethernet connection to data link machine performance to customers local area network and internal management systems
- Printer for hard copy read out
- USB access for alternative data capture and transfer
- All materials are FDA approved and comply with Article 16 (1) of Regulation (EC) number 1935/2004, ad Article 15 of Regulation 10/2011

Model	PASTA 1 - CCW-RV-214W-1S-30-SS-PST1		
Max Piece Length	100mm		
Target Volume*	<1.35 litres	>3.15 litres	
Top Speed*	100 WPM	40 WPM	
Contact Parts Finish	Hex contact parts on top of machine (better control), plain finished contact parts (to promote free flow of product and prevent dust build up), liners included for particularly fragile products		
Dispersion Table	Plain finish 10° dispersion table with skirt (to reduce spillage)		
Ring Gate	Included with blue metal-detectable polyurethane fingers (controlling product infeed)		
Radial Feeder Troughs	Hex embossed semi-separated, 30mm 30° raised lip for fine pasta (due to free flowing nature of product)		
Hoppers	Double opening, plain finish, anti-leak flared back pool hoppers, single opening, plain finish anti-leak weigh hopper with baffle plates and blue metal-detectable polyurethane end lip. All hoppers supplied with blue metal-detectable polyurethane liners (as option for delicate pasta)		
Discharge Chutes	53° discharge chute with lower anti-swirl fins and upper flat blue metal-detectable polyurethane inserts and cushion pipe fitted		
Timing Hopper	6 litres motor driven timing hopper included with cover and fitted with liners Options: Double opening, diverting or error diverting		
Software	Multiple languages available, count priority, enhanced average weight control, error signal output, auto zero cleaning mode, remote diagnostics software		

*figures are based on historical application products and may vary depending on specific nature of produc











ISHIDA EUROPE LIMITED
Kettles Wood Drive
Woodgate Business Park
Birmingham
B32 3DB
United Kingdom
Tel: +44 (0)121 607 7700
Fax: +44 (0)121 607 7888
info@ishidaeurope.com

ISHIDA CZECH REPUBLIC
Tel: +420 317 844 059
Fax: +420 317 844 052
info@ishidaeurope.cz

ISHIDA ROMANIA
Tel: +40 (0)21 589 73 52
Fax: +40 (0)21 310 34 22
info@ishidaeurope.ro

ISHIDA FRANCE
Tel: +33 (0)1 48 63 83 83
Fax: +33 (0)1 48 63 24 29
info@ishidaeurope.fr

ISHIDA RUSSIA AND CIS Tel: +7 499 272 05 36 Fax: +7 499 272 05 37 info@ishidaeurope.ru ISHIDA GERMANY
Tel: +49 (0)791 945

Tel: +49 (0)791 945 160 Fax: +49 (0)791 945 1699 info@ishida.de

ISHIDA SOUTH AFRICA
Tel: +27 (0)11 976 2010
Fax: +27 (0)11 976 2012
info@ishidaeurope.com

ISHIDA MIDDLE EAST Tel: +971 (0)4 299 1933

Fax: +971 (0)4 299 1955 ishida@ishida.ae

ISHIDA SWITZERLAND Tel: +41 (0)41 799 7999 Fax: +41 (0)41 790 3927

info@ishida.ch

ISHIDA NETHERLANDSTel: +31 (0)499 39 3675
Fax: +31 (0)499 39 1887

927

info@ishida.nl