

Semi-Automatic Tape Sealer Up to 30 cases per minute




Semi-Automatic Case Taper



Squareness Assured

BEL's innovative and powerful Uni-Drive system synchronizes conveyor belt speed, eliminating case skew, so that cases leave the machine squarely taped.



Lasting Performance


The BEL 150 features heavy duty, corrosion resistant aluminum C-Beam construction and compact design to provide lasting performance in the most demanding production environments.



Superior Tape Application The BEL 150 is equipped

with state-of-the-art DEKKA High Performance stainless steel tape heads that are easily loaded in or out of the machine in 30 seconds or less.





3EL 150



BEL 150 Semi-Automatic Top and Bottom Case Taper

BEL 150 Features

- Paint free, corrosion resistant frame, guards against contamination from flaking or peeling paint
- Built-in safety systems that protect against power interruption or overload
- Uni-Drive squaring mechanism that mean more presentable cases
- Quick and easy maintenance, meaning a minimum of downtime
- Standard DEKKA 22 Stainless Steel 2" tape heads and optional DEKKA 3" tape heads available

Complete Solution



BEL 505 Case Former

The BEL 505 improves efficiency and ergonomics. Inserting a case into the BEL 505 results in all four bottom flaps being automatically folded, leaving hands free to pack.



BEL 150X Oversize Case Taper The oversize model is available to accommodate larger case requirements.




BEL 150SS Stainless Steel Case Taper The stainless steel is available for washdown environments.

BEL 150 Specifications

Case Size Range	Length	Width	Height	
Minimum	8" 203 mm	5 1/2" 140 mm	4" 89 mm	
Maximum	unlimited	17 3/8" 441 mm	21" 533 mm	
Infeed/Outfeed Height (with adjustable foot pads) Note: Castors add 6" to minimum and maximum height.				
Minimum	23 1/2" (597 mm)			
Maximum	32" (813 mm)			
Machine Speed: Up to 30 Oversize model available.	•		nges.	

Specifications are subject to change without notice.

How the BEL 150 Works





1 Quick Change Handle

Upper assembly is adjusted with a hand wheel which increases or reduces size in seconds.



2 Uni-Drive Case Transport

Uni-drive system synchronizes the case conveyor, assuring case squareness during taping.



3 Top & Bottom Sealed

Superior case sealing performance is achieved with its quality tape application. The BEL 150 comes standard with DEKKA tape heads.



Wexxar Packaging Inc. 10101 Nordel Court Delta, BC Canada V4G 1J8 Phone: 604-930-9300 Fax: 604-930-9368 Email: sales@wexxar.com Web: www.wexxar.com



Backed by Wexxar's warranty and experienced, nationwide service team.



Oversize Semi-Automatic Tape Sealer Up to 30 cases per minute




Oversize Semi-Automatic Case Taper



Squareness Assured

BEL's innovative and powerful Uni-Drive system synchronizes conveyor belt speed, eliminating case skew, so that cases leave the machine squarely taped.



Lasting Performance

The BEL 150X features heavy duty, corrosion resistant aluminum C-Beam construction and compact design to provide lasting performance in the most demanding production environments.



Superior Tape Application The BEL 150X is equipped

with state-of-the-art DEKKA High Performance stainless steel tape heads that are easily loaded in or out of the machine in 30 seconds or less.



Easy Case Change

The BEL 150X is userfriendly, enabling the operator to make box size changes from either side of the machine quickly and easily, in 30 seconds or less.



BEL 150X Oversize Semi-Automatic Case Taper

BEL 150X Features

- Paint free, corrosion resistant frame, guards against contamination from flaking or peeling paint
- Built-in safety systems that protect against power interruption or overload
- Uni-Drive squaring mechanism that mean more presentable cases
- Quick and easy maintenance, meaning a minimum of downtime
- Standard DEKKA 22 Stainless Steel 2" tape heads and optional DEKKA 3" tape heads available

Complete Solution



BEL 505 Case Former

The BEL 505 improves efficiency and ergonomics. Inserting a case into the BEL 505 results in all four bottom flaps being automatically folded, leaving hands free to pack.



BEL 150 Case Taper

Semi-automatic case taper that accepts uniform case sizes for top and bottom case sealing.



BEL 150SS Stainless Steel Case Taper The stainless steel is available for washdown environments.

How the BEL 150X Works







1 Quick Change Handle

Upper assembly is adjusted with a hand wheel which increases or reduces size in seconds.



2 Uni-Drive Case Transport

Uni-drive system synchronizes the case conveyor, assuring case squareness during taping.



3 Top & Bottom Sealed

Superior case sealing performance is achieved with its quality tape application. The BEL 150X comes standard with DEKKA tape heads.

BEL 150X Specifications

Case Size Range	Length	Width	Height	
Minimum	8" 203 mm	6 1/2" 165 mm	5" 127 mm	
Maximum	unlimited	25 1/2" 648 mm	30" 762 mm	
Infeed/Outfeed Height (with adjustable foot pads) Note: Castors add 6" to minimum and maximum height.				
Minimum	19 1/2" (495 mm)			
Maximum	28" (711 mm)			
Machine Speed: Up to 30 cases per minute. Oversize model available. Consult factory for case size ranges.				



Wexxar Packaging Inc. 10101 Nordel Court Delta, BC Canada V4G 1J8 Phone: 604-930-9300 Fax: 604-930-9368 Email: sales@wexxar.com Web: www.wexxar.com



Specifications are subject to change without notice.

Backed by Wexxar's warranty and experienced, nationwide service team.