

 **First in Quality. Built to Last.**



SHRINK TUNNELS

PROFESSIONAL SERIES

EVERLASTING SHRINK PERFORMANCE
EASTEY Professional Series Shrink Tunnels are the ultimate workhorse for your most abusive shrink applications.

MODELS

ET2008, ET2012, ET2016, ET2020, ET2408, ET2412, ET2416, ET2420, ET3608, ET3612, ET3616, ET3620, ET4808, ET4812, ET4816, ET4820, ET5608, ET5612, ET5616, ET5620, ET7008, ET7012, ET7016, ET7020

DURABILITY THAT CAN'T BE MATCHED


EASTEY's Professional Series Shrink Tunnels provide top of the line features and the most robust tunnel design on the market today. Expertly welded from 12 gauge cold rolled steel, EASTEY Professional Series Shrink Tunnels will withstand even the most abusive real world shrink wrap applications. As a measure of strength, EASTEY tunnels weigh nearly twice as much as competitive models.

PROVEN RELIABILITY FOR YOUR NEEDS

They are designed and built to give you all the performance features needed for positive shrinking a wide variety of films including polyolefin, polyethylene, and PVC. Variable four-direction air flow, variable air velocity and delayed cool down are just some of the features that provide the durability you have come to rely on from EASTEY. See for yourself why EASTEY has been a leader in the shrink packaging industry for over 25 years.

STANDARD FEATURES

- Designed to shrink most polyolefin, polyethylene, and PVC shrink films
- All-welded main frame from 12 gauge cold rolled steel
- Live roller, "dead" roller, or stainless steel mesh belt conveyor standard; optional plastic belt conveyor
- Sealed bearings (not bushings) on drive and idler shafts
- Adjustable digital solid state temperature control for a variety of films
- Four-directional air flow provides positive shrinking
- Variable air flow for a variety of products and applications
- Large ducting creates more air volume inside tunnel
- Plugs available for patterned air flow
- Delayed cool down and over temperature protection
- Fold down electrical control panel for easy maintenance
- Live roller conveyor speed up to 67 fpm, mesh belt conveyor speed up to 100 fpm
- Heavy duty casters for transportation within plant
- Leveling legs provide sturdy base once in place
- Custom two part epoxy finish resists scratching
- Stainless steel models available on ET20
- 220v 3-phase standard, some models available in 480v 3-phase
- Easy to use design requires minimal training, maintenance, and trouble free operation
- Made in the USA



1. **Mesh belt**
Stainless steel mesh belt conveyor provides maintenance free operation
2. **Live Roller**
Live roller conveyor provides a more finished look for retail packaging applications
3. **Control panel**
Easy to use control panel lets users adjust for their specific application
4. **Air flow knob**
Variable air flow adjustments at your fingertips
5. **Inside of tunnel**
Four directional air flow provides positive shrinking
6. **Shrunk box coming out of tunnel**
Positive shrinking on most polyolefin, polyethylene and PVC films

MODEL NUMBER	MACHINE DIMENSIONS			CHAMBER DIMENSIONS			CONVEYOR		STANDARD POWER			WEIGHT	
	WIDTH (A)	HEIGHT (B)	LENGTH (C)	WIDTH	HEIGHT	LENGTH	WIDTH	LENGTH	VOLTS	AMPS	PHASE	WEIGHT	SHP WT.
ET20	33"	56"-72"	74"	20"	4"-20"	52"	20"	72"	220	50	3	900 lbs 410 kg	1200 lbs 546 kg
ET24	37"	56"-72"	74"	24"	4"-20"	52"	24"	72"	220	50	3	1000 lbs 455 kg	1250 lbs 569 kg
ET36	49"	56"-72"	74"	36"	4"-20"	52"	36"	72"	220	50-60	3	1300 lbs 591 kg	1600 lbs 728 kg
ET48	61"	56"-72"	74"	48"	4"-20"	52"	48"	72"	220	80-90-110	3	1700 lbs 773 kg	2000 lbs 910 kg
ET56	69"	56"-72"	74"	56"	4"-20"	52"	56"	72"	220	90-110	3	2000 lbs 910 kg	2300 lbs 1047 kg
ET70	83"	56"-72"	74"	70"	4"-20"	52"	70"	72"	220	90-100	3	2500 lbs 1138 kg	2800 lbs 1274 kg



7041 Boone Avenue North, Brooklyn Park, MN 55428
 (763) 428-4846 1 (800) 835-9344
 www.eastey.com info@eastey.com

